

Fiber Optic Distribution Box 48 ports



Description

SOFTEL Model No. NAP-48S, this distribution box can realize the functions of fiber fusion, distribution and scheduling in the FTTH system. This fiber box is made of new ABS material, and its shell is strong and durable. And IP65's protection rating allows it to be installed and used outdoors. Internally, this kind FDB can also be fitted with a variety of stents to install adapters, mini steel splitter or cassette splitter.

Product Specifications

Item	Fiber Optic Distribution Box 48 ports
Dimension	360*260*120mm
Material	PC+ABS
Weight	1.65kg
No. of Cable Inlet/Outlet	2 IN-24OUT
Diameter of Cable	IN: 7mm-15mm OUT: 2-12mm
Adaptor accommodating	Max.48 port of SC, FC, LC
Splitter	One for 1x16 splitter
Working Temperature	-30deg.C~60deg.C
Protection Grade	IP65

Ordering Information

FiberNex PN	Capacity (single core)	Adaptor type	Description
-------------	---------------------------	--------------	-------------

NAP-48S xxP	xx Port	SC	Fiber Optic Subscriber Distribution box xx Port SC type
NAP-48S xxP	xx Port	FC	Fiber Optic Subscriber Distribution box xx Port FC type
NAP-48S xxP	xx Port	LC	Fiber Optic Subscriber Distribution box xx Port LC type

*Does not including adaptors, pigtails and splitter. Additional configurations can be made if required

Product physical drawing



Type of installation



Accessories for pole mounted are not included as standard and require additional costs.

Packing Info:

Carton packing: 10sets/carton

Carton size: 67*37*56cm

Weight: 17.5kg/carton