



B2



B3

## SR RACK-MOUNT ENCLOSURES

- Standard 19".
- Cold rolled steel sheet as raw material.
- Versatile panel with extendable double slide rails for smooth sliding.
- 1RU installs 2pcs standard adapter plates at different types.
- Front saddles pivot for improved patch cord routing and organization.
- Comprehensive accessory kit for cable entry and fiber management.
- Patch cord bend radius guides minimize macro bending.
- Different 175-adapter interface including ST, SC, FC, LC, etc.
- Splice capability is up to Max. 48 fibers with splice trays loaded .
- Full assembly (loaded) or empty panel.

## SR RACK-MOUNT ENCLOSURES

Description	Maximum Capacity			Part NO.
	Adapter(SC/LC/FC/ST)	Adapter Plates	Splice Tray	
SR 1U empty	36/48/36/36	2	2	ODF-B2


## PACKING INFORMATION

Description	ODF-B2
Product Dimension	430*327*1U
Packing Dimension	490*370*50
Master Carton Dimension	510*390*50
Master Carton Capacity	5pcs


# Rack Mount | ODF-B



A



B



C

## ACCESSORIES

### Description

A Type-C Splice Tray , 1piece can splice 24 fibers.

B 175-Adapter,install 12 Simplex FC adapters / 12 Simplex ST adapters

C 175-Adapter,install 12 Simplex SC adapters / Duplex LC adapters

## SPOTLIGHT



Pull out design enhances flexibility. You can order an empty customized fiber enclosure from OTRANS. Alternatively, your order can arrive in one box, with your adapter plates & adapters, and splice trays already installed just as you required.